PCT

WORLD INTELLECTUAL PROPERTY ORGANIZATION International Bureau



INTERNATIONAL APPLICATION PUBLISHED UNDER THE PATENT COOPERATION TREATY (PCT)

(51) International Patent Classification 5:

(11) International Publication Number:

WO 91/12500

G01J 3/52, B41M 1/18

A1

(43) International Publication Date:

22 August 1991 (22.08.91)

(21) International Application Number:

PCT/GB91/00204

(22) International Filing Date:

8 February 1991 (08.02.91)

(30) Priority data: 9002962.0

9 February 1990 (09.02.90) GB

(71) Applicant (for all designated States except US): GORDON PHILLIPS LIMITED [GB/GB]; Springwater House, Taffs Well, Cardiff CF4 7QR (GB).

(72) Inventor; and

(75) Inventor/Applicant (for US only): PHILLIPS, Gordon, Leslie, Price [GB/GB]; 243 Cyncoed Road, Cardiff, Glamorgan CF2 6NY (GB).

(74) Agents: JAMES, Michael, John, Gwynne et al.; Wynne-Jones, Laine & James, Morgan Arcade Chambers, 33 St. Mary Street, Cardiff CF1 2AB (GB). (81) Designated States: AT (European patent), AU, BE (European patent), CH (European patent), DE (European patent), DK (European patent), ES (European patent), FR (European patent), GB (European patent), GR (European patent), IT (European patent), JP, LU (European patent), NL (European patent), SE (European patent), US.

Published

With international search report.

Before the expiration of the time limit for amending the claims and to be republished in the event of the receipt of amendments.

(54) Title: IMPROVEMENTS RELATING TO COLOUR MEASUREMENT

(57) Abstract

A colour referencing system is provided whereby a process colour is first defined in terms of percentage levels of a number of base colours to create a standard reference, an ink mixture is experimentally defined for a flat colour which corresponds in appearance to the process colour and the CIELAB or other colour difference equation value is determined by conventional means for that matched colour. Such a system is only possible if the process colour reference standard can be repeated without error. The illustration of the process colours in relation to their standard reference is therefore ideally achieved by the system as is deroduce this exactly as a process colour by a predetermined combination of four colours using particular screened percentage values.

÷ ,-, -

FOR THE PURPOSES OF INFORMATION ONLY

Codes used to identify States party to the PCT on the front pages of pamphlets publishing international applications under the PCT.

| AT | Austria | ES | Spain | MG | Madagascar |
|-----|--------------------------|-----|------------------------------|------|----------------------------|
| AU | Australia | FI | Finland | · ML | Mali |
| BB. | Barbados | FR | France | MN | |
| BE | Belgium · | GA | Gabon | | Mongolia |
| BF | Burkina Faso | GB | United Kingdom | MR | Mauritania |
| BG | Bulgaria | GN | Guinca Kingdoni | MW | Malawi |
| BJ | Benin | GR | | NL | Netherlands |
| BR | Brazil | | Greece | NO | Norway |
| CA | Cànada | HU | Hungary | PL | Poland |
| CF | Central African Republic | ıτ | Italy | RO | Romania |
| CG | • | JP | Japan | SD | Sudan |
| | Congo | KP | Democratic People's Republic | SE | Sweden |
| CH | Switzerland | | of Korea | SN | Senegal |
| CI | Côte d'Ivoire | KR | Republic of Korea | su | Soviet Union |
| CM | Cameroon | LI | Liechtenstein | TD | Chad . |
| CS | Czechoslovakia | LK' | Sri Lanka | TG | Togo |
| DE | Germany | LU. | Luxembourg | us | . United States of America |
| DK | Denmark | MC | Monaco | 00 | . Cinco salo o Allenta |

"Improvements Relating to Colour Measurement"

In printing, colours can be produced in two ways:

- (1) By using pigmented inks in a range only limited by the availability of pigments, to produce so called flat or solid colours by a single mix.
- (2) By printing a smaller set of these colours using for example only the pigmented colours of cyan, magenta and yellow together with black. This method produces colours by using solid and/or screened values defined in percentage terms of the four inks superimposed one on the other. These are so called process colours.

Conventionally colours can be measured by means of one of various types of colour difference equations to give colorimetric values by a standard code such as that known as CIELAB numbers. This particular classification incorporates a combination of three factors which create a particular visual effect of a colour namely, (A) its hue, (B) pigment saturation level or degree of separation and (L) the degree of lightness which is a function of the ink thickness or density. The CIELAB standard for any particular colour can 20 be measured by a number of known existing scientific methods. CIELAB numbers can be calculated from colours produced by either of the above methods. While such a code, if identical for two colours produced by both methods, would indicate that the colours are the same, there is no simple 25 method of defining both the ink mix for the flat colour and the percentage values for the process colour which would be

necessary to achieve these equivalent results.

Moreover it can be shown that although it is possible to start with a process colour and duplicate this as a flat colour by finding a given ink mix to achieve the same CIELAB numbers, the reverse is not true. There is no known method by which it is possible to start from a flat colour produced by the first method and reproduce this exactly as a process colour by any combination of the four colours using screened percentages of any value.

Whereby an adequate reference system of printed process colours can be duplicated by single ink flat colours to the same visual appearance and substantially identical colour difference equation values. Such a system then provides a simple means of producing a range of colours by either method without further calculation. This would enable a printer to create a flat colour which is equivalent to a process colour being used (and vice versa), where colour matching is necessary when printed material is being produced by differing methods.

Accordingly this invention provides a colour referencing system whereby a process colour is first defined in terms of percentage levels of a number of base colours to create a standard reference, an ink mixture is experimentally defined for a flat colour which corresponds in appearance to the process colour and the colour difference equation value is determined by conventional means for that matched colour.

25

Such a system is only possible if the process colour reference standard can be repeated without error. The illustration of the process colours in relation to their standard reference will ideally be by the system as is defined in our existing European Patent Number 0119836.

In determining the equivalent flat colour for a particular process colour a spectrophotometer could be used to give an approximate measurement of the process colour and a possible flat colour mix could be calculated by a suitably programmed computer. This might give a number of possible 10 choices of mixes of pigment to make a flat colour. These can be prepared and then compared by eye with the process A skilled operator can then make the necessary colour. small adjustments to the mixes to bring the flat colour as close in appearance to the process colour as it is possible 15 to judge by eye.

An advantage of this method is that the number of pigments required for ink mixing purposes for the process colour method is largely confined to three or four colours. A most important advantage is that both sets of colours can 20 be precisely defined in colorimetric values by their CIELAB codes. A further advantage is that the CIELAB value of the basic inks CYAN, MAGENTA, YELLOW and BLACK are precisely maintained to existing major international colour standards which are closely monitored and strongly supported.

It has already been shown that the particular process colour arrangement of European Patent Number 0119836 allows for percentage specifications to be adjusted for a number of

WO 91/12500

10

15

25

4

differing printing conditions in order that the reference process colour remains the same. Similarly it is possible to achieve the same colours by the flat colour method by adjusting ink formulations to allow for printing conditions which change by reason of differing substrates. Thus further calculations can be made to allow for circumstances which will vary the appearance of a colour. For example, a flat colour mix will give a different appearance when applied to coated stock paper as compared to its use on unprepared stock paper. The formula for the required flat colour (and its relevant CIELAB number) could be calculated separately depending on whether the colour is to be applied to coated or uncoated stock paper.

There could also be a variation in dot gain for the process colour depending upon the screen size and other printing factors, such as the ability of the paper to absorb the ink. Calculations could be made therefore to determine modifications of the percentages of the base colours used, for particular operational variations, to create a desired process colour which has the required visual similarity to the flat colour having a particular defined CIELAB number.

Once the required referencing of the process colours to flat colours, and variations for differing printing conditions and substrates, has been determined, in order to relate the colours formed by the two processes to the relevant CIELAB number, various additional systems can be envisaged. For example look-up tables can be created for various paper stocks to which the colours may be applied.

The user can then select the correct formulation for a particular colorimetric value as defined by the relevant CIELAB number for a particular paper stock. Furthermore, programming control of the print heads of the printing press is possible to adjust the ink levels digitally to create a colour having the required CIELAB number. Indeed, the print head control could be determined from a direct reading from a spectrophotometer and densitometer applied to a particular colour which is to be matched. The reading (equivalent to a particular CIELAB number) will then be used as the control 10 parameter to program the print heads outputs. This applies to the creation of both the process colour or the flat colour, for which suitable software control programs can be created and correlated with one another. This control is normally measured by density. The present concept therefore allows for better calibration and control of the printing machine.

It will be appreciated that the comparison with a standard set of printed process colour references may be made by this invention not only with other printed colours but also with colours achieved by any process. Also the system may be used for process colours created not only by dot screen printing but also by line printing such as with a laser printer.

Whilst reference has been made throughout the specification to CIELAB numbers, this is merely one particular system of a colour difference equation (although it is presently the most popular) from several which are used in

the printing industry. Consequently, where the term CIELAB number or value is used this is intended to imply any standard number or value as defined by any colour difference or transformation equation which provides an adequate evaluation of a range of colours for which a correlation between the process colour and the flat colour is required.

25

4.

CLAIMS

- 1. A colour referencing system whereby a process colour is first defined in terms of percentage levels of a number of base colours to create a standard reference, an ink mixture is experimentally defined for a flat colour which corresponds in appearance to the process colour and the colour difference equation value is determined by conventional means for that matched colour.
- A system according to claim 1, wherein the illustration of the process colours in relation to their standard reference is by the system as is defined in European Patent Number 0119836.
- 3. A system according to claim 1 or claim 2, wherein a spectrophotometer is used to give an approximate measure-15 ment of the process colour and possible flat colour mixes are calculated, such as by a suitably programmed computer, prepared and compared by eye with the process colour, with any necessary small adjustments to the mixes being made to bring the flat colour as close in appearance to the process colour as it is possible to judge by eye.
 - A system according to any one of claims 1 to 3, wherein ink formulations are adjusted to allow for printing conditions which change by reason of differing substrates, or by variation in dot gain for the process colour depending upon the screen size and other printing factors.
 - A system according to claim 4, wherein look-up 5. tables are created for various paper stocks to which the

colours may be applied.

- 6. A system according to any one of claims 1 to 5, wherein programming control of the print heads of the printing press is provided to adjust the ink levels digitally to create a colour having the required colour difference equation number.
- 7. A system according to claim 6, wherein the print head control is determined from a direct reading from a spectrophotometer and densitometer applied to a particular colour which is to be matched.
 - 8. A system according to claim 7, wherein the reading is used as the control parameter to program the print heads outputs.
- 9. A colour referencing system according to claim 1, 15 and substantially as herein described.

International Application No PCT/GB 91/00204

| | IFICATION OF SUBJECT MATTER (If several class | | |
|------------------|---|--|---|
| | to International Patent Classification (IPC) or to both Nat | ional Classification and IPC | • |
| IPC : | Ġ 01 J 3/52, B 41 M 1/18 | | |
| II. FIELDS | SEARCHED | | |
| | Minimum Docume | ntation Searched 7 | |
| Classification | on System | Classification Symbols | , |
| 5 | | | |
| IPC ⁵ | B 41 F, B 41 M, B 4 | 4 D, G 01 J | |
| · | <u> </u> | | |
| | Documentation Searched other to the Extent that such Documents | than Minimum Documentation are included in the Fields Searched | |
| | | | |
| | | | |
| III. DOCU | MENTS CONSIDERED TO BE RELEVANT | | |
| Category • | Citation of Document, 11 with Indication, where app | copriate, of the relevant passages 12 | Relevant to Claim No. 13 |
| | | | |
| A | EP, A, 0119836 (GORDON PH | ILLIPS) | 1-4,9 |
| İ | 26 September 1984 | | |
| | see abstract; page 9, | | |
| ! | 15, lines 7-14; page cited in the application | 19, lines 3-12 | 1 |
| į | creed in the abbitcation | | |
| A | EP, A, 0324718 (GRETAG) | | 6-8 |
| 1 | 19 July 1989 | | |
| İ | see page 3, lines 38- | 52; page 4, | |
| | lines 6-13; figure 1 | | |
| A | Deutsche Normon, DIN 1652 | 0 0 1071 | |
| . ^ | Deutsche Normen: DIN 1653 "Europäische Farbskal | a für den Offset- | 1,3 |
| 4 | druck" | d rur den orrset- | |
| · · j | see the whole documen | t | |
| | | _ | |
| A . | Journal of the Optical So | ciety of America, | 1 |
| · j | vol. 68, no. 8, Augus Society of America, | t 1978, Optical | |
| . | H.R. Davidson: "Prepa | ration of the OSA | |
| | uniform color scales | committee samples". | |
| į | pages 1141-1142 | , , , , , , , , , , , , , , , , , , , | |
| } | see page 1141, left-h | and column, | |
| . Special | paragraph 2 | | <u> </u> |
| "A" docu | ment defining the general state of the art which is not | or priority date and not in conflict | ct with the application but |
| • | idered to be of particular relevance or document but published on or after the international | cited to understand the principle invention | |
| filing | date | "X" document of particular relevant cannot be considered novel or | ca; the claimed invention cannot be considered to |
| · which | ment which may throw doubts on priority claim(s) or h is cited to establish the publication date of another | involve an inventive step "Y" document of particular relevant | e: the claimed lovention |
| "O" docu | on or other special reason (as specified) ment referring to an oral disclosure, use, exhibition or | cannot be considered to involve a document is combined with one | an inventive step when the or more other such docu- |
| other | r means ment published prior to the international filing date but | ments, such combination being o | bylous to a person skilled |
| | than the priority date claimed | "&" document member of the same p | eatont family |
| IV. CERTI | | | |
| Date of the | Actual Completion of the International Search | Date of Mailing of this International Se | |
| | 3rd May 1991 | 2 1 J | UN 1991' |
| Internationa | I Searching Authority | Signature of Authorized Officer | 0/10 |
| | EUROPEAN PATENT OFFICE | 110 | 112 |
| | - CONCIDENT PAIDING OFFICE | - Thice | T TATEL AAR |

ANNEX TO THE INTERNATIONAL SEARCH REPORT ON INTERNATIONAL PATENT APPLICATION NO.

SA

This annex lists the patent family members relating to the patent documents cited in the above-mentioned international search report.

The Function Patent Office EDP file on 19/06/91

| The European Patent Office is in no way fight from the | on 19/06/91 |
|--|---|
| The European Patent Office is in no way liable for these particulars where | hich are merely given for the number of the |
| • | Broad for the purpose of information. |

| Patent document cited in search report | | | nt family mber(s) | Publication date |
|--|----------|-------------------------|-------------------------------|----------------------------------|
| EP-A- 0119836 | 26-09-84 | US-A- | 4629428 | 16-12-86 |
| EP-A- 0324718 | 19-07-89 | JP-A- US-A- AU-A- | 1225554 4975862 2851989 | 08-09-89 04-12-90 20-07-89 |